

## **RC4558**

# **Dual High-Gain Operational Amplifier**

### **Description**

The 4558 integrated circuit is a dual high-gain operational amplifier internally compensated and constructed on a single silicon IC using an advanced epitaxial process.

Combining the features of the 741 with the close parameter matching and tracking of a dual device on a monolithic chip results in unique performance characteristics. Excellent channel separation allows the use of this dual device in dense single 741 operational amplifier applications. It is especially well suited for applications in differential-in, differential-out as well as in potentiometric amplifiers and where gain and phase matched channels are mandatory.


### **Features**

- ◆ 2.5 MHz unity gain bandwidth
- ◆ Supply voltage  $\pm 22V$  for RM4558 and  $\pm 18V$  for RC/RV4558
- ◆ Short-circuit protection
- ◆ No frequency compensation required
- ◆ No latch-up
- ◆ Large common-mode and differential voltage ranges
- ◆ Low power consumption
- ◆ Parameter tracking over temperature range
- ◆ Gain and phase match between amplifiers

# RC4558


## Connection Information

8-Lead  
TO-99 Metal Can  
(Top View)




65-0209

8-Lead  
Dual In-Line Package  
(Top View)



65-0210

8-Lead Plastic  
Dual In-Line SO-8  
(Top View)



65-02666

Pin	Function
1	Output (A)
2	-Input (A)
3	+Input (A)
4	-V <sub>S</sub>
5	+Input (B)
6	-Input (B)
7	Output (B)
8	+V <sub>S</sub>

## Ordering Information

Part Number	Package	Operating Temperature Range
RC4558M	M	0°C to +70°C
RC4558N	N	0°C to +70°C
RM4558D	D	-55°C to +125°C
RM4558D/883B	D	-55°C to +125°C
RM4558T	T	-55°C to +125°C

### Notes:

/883B suffix denotes Mil-Std-883, Level B processing

N = 8-lead plastic DIP

D = 8-lead ceramic DIP

T = 8-lead metal can (TO-99)

M = 8-lead plastic SOIC

## Absolute Maximum Ratings

### Supply Voltage

RM4558 ..... ±22V

RC4558 ..... ±18V

Input Voltage<sup>1</sup> ..... ±15V

Differential Input Voltage ..... 30V

Output Short Circuit Duration<sup>2</sup> ..... Indefinite

Operating Temperature Range

RM4558 ..... -55°C to +125°C

RC4558 ..... 0°C to +70°C

Lead Soldering Temperature

(SO-8; 10 sec) ..... +260°C

Lead Soldering Temperature

(DIP, TO-99; 60 sec) ..... +300°C

### Notes:

1. For supply voltages less than -15V, the absolute maximum input voltage is equal to the supply voltage.

2. Short circuit may be to ground on one op amp only. Rating applies to +75°C ambient temperature.

**Thermal Characteristics**

	<b>8-Lead Small Outline</b>	<b>8-Lead Plastic DIP</b>	<b>8-Lead Ceramic DIP</b>	<b>8-Lead TO-99 Metal Can</b>
Max. Junction Temp.	+125°C	+125°C	+175°C	+175°C
Max. $P_D$ $T_A < 50^\circ\text{C}$	300 mW	468 mW	833 mW	658 mW
Therm. Res $\theta_{JC}$	—	—	45°C/W	50°C/W
Therm. Res. $\theta_{JA}$	240°C/W	160°C/W	150°C/W	190°C/W
For $T_A > 50^\circ\text{C}$ Derate at	4.17 mW/°C	6.25 mW/°C	8.33 mW/°C	5.26 mW/°C

**Matching Characteristics**(V<sub>S</sub> = ±15V, T<sub>A</sub> = +25°C unless otherwise specified)

Parameter	Test Conditions	RM/RC4558 Typ	Units
Voltage Gain	R <sub>L</sub> ≥ 2 kΩ	±1.0	dB
Input Bias Current	R <sub>L</sub> ≥ 2 kΩ	±15	nA
Input Offset Current	R <sub>L</sub> ≥ 2 kΩ	±7.5	nA

# RC4558

## Electrical Characteristics







( $V_S = \pm 15V$  and  $T_A = +25^\circ C$  unless otherwise specified)

Parameters	Test Conditions	RM4558			RC4558			Units
		Min	Typ	Max	Min	Typ	Max	
Input Offset Voltage	$R_S \leq 10k\Omega$		1.0	5.0		2.0	6.0	mV
Input Offset Current			5.0	200		5.0	200	nA
Input Bias Current			40	500		40	500	nA
Input Resistance		0.3	1.0		0.3	1.0		MΩ
Large Signal Voltage Gain	$R_L \geq 2k\Omega, V_{OUT} = \pm 10V$	50	300		20	300		V/mV
Output Voltage Swing	$R_L \geq 10k\Omega$	±12	±14		±12	±14		V
	$R_L \geq 2k\Omega$	±10	±13		±10	±13		V
Input Voltage Range		±12	±13		±12	±13		V
Common Mode Rejection Ratio	$R_S \leq 10k\Omega$	70	100		70	100		dB
Power Supply Rejection Ratio	$R_S \leq 10k\Omega$	76	100		76	100		dB
Power Consumption	$R_L = \infty$		100	170		100	170	mW
Transient Response	$V_{IN} = 20 mV$							
	$R_L = 2k\Omega$		0.3			0.3		μS
	$C_L \leq 100pF$		35			35		%
Slew Rate	$R_L \geq 2k\Omega$		0.8			0.8		V/μS
Channel Separation	$F = 10kHz, R_S = 1k\Omega$		90			90		dB
Unity Gain Bandwidth (Gain = 1)		2.5	3.0		2.0	3.0		MHz

The following specifications apply for  $RM = -55^\circ C \leq T_A \leq +125^\circ C$ ,  $RC = 0^\circ \leq T_A \leq +70^\circ C$

Input Offset Voltage	$R_S \leq 10k\Omega$			6.0			7.5	mV
Input Offset Current				500			300	nA
RC4558				1500			800	nA
Input bias Current								
RC4558								
Large Signal Voltage Gain	$R_L \geq 2k\Omega, V_{OUT} = \pm 10$	25			15			V/mV
Output Voltage Swing	$R_L \geq 2k\Omega$	±10			±10			V
Power Consumption	$R_L = \infty$		120	200		120	200	mW


## Typical Performance Characteristics




# RC4558

## Typical Performance Characteristics (Continued)


Output Voltage Swing vs. Supply Voltage




Output Voltage Swing vs. Load Resistance




Output Voltage Swing vs. Frequency




Quiescent Current vs. Supply Voltage








Transient Response  
Output Voltage vs. Time



Follower Large Signal Pulse Response  
Output Voltage vs. Time



## Typical Performance Characteristics (Continued)




Linear

# RC4558


## Typical Applications

Voltage Follower




65-0228

Lamp Driver




65-0229

Power Amplifier




65-0230

Comparator With Hysteresis



65-0231


Squarewave Oscillator




65-0232

## Typical Applications (Continued)


DC Coupled 1kHz Low-Pass Active Filter




AC Coupled Non-Inverting Amplifier




1kHz Bandpass Active Filter



AC Coupled Inverting Amplifier




Voltage Controlled Oscillator (VCO)



# RC4558

## Schematic Diagram



65-0208

## **RC4559**

# **High-Gain Dual Operational Amplifier**

### **Description**

The 4559 integrated circuit is a high performance dual operational amplifier internally compensated and constructed on a single silicon chip using an advanced epitaxial process.

These amplifiers feature guaranteed AC performance which far exceeds that of the 741-type amplifiers. The specially designed low-noise input transistors allow the 4559 to be used in low-noise signal processing applications such as audio preamplifiers and signal conditioners.

The 4559 also has more output drive capability than 741-type amplifiers and can be used to drive a  $600\Omega$  load.


### **Features**

- ◆ Unity gain bandwidth — 4.0 MHz
- ◆ Slew rate — 2.0 V/ $\mu$ S
- ◆ Low noise voltage — 1.4  $\mu$ V<sub>RMS</sub>
- ◆ Supply voltage —  $\pm 22V$  for RM4559 and  $\pm 18V$  for RC/RV4559
- ◆ No frequency compensation required
- ◆ No latch up
- ◆ Large common mode and differential voltage ranges
- ◆ Low power consumption
- ◆ Parameter tracking over temperature range
- ◆ Gain and phase match between amplifiers

# RC4559


## Connection Information

8-Lead  
TO-99 Metal Can  
(Top View)




65-0209

8-Lead  
Dual In-Line Package  
(Top View)



65-0210

8-Lead Plastic  
Dual In-Line SO-8  
(Top View)



65-02668

Pin	Function
1	Output (A)
2	-Input (A)
3	+Input (A)
4	-V <sub>S</sub>
5	+Input (B)
6	-Input (B)
7	Output (B)
8	+V <sub>S</sub>

## Ordering Information

Part Number	Package	Operating Temperature Range
RC4559M	M	0°C to +70°C
RC4559N	N	0°C to +70°C
RC4559D	D	0°C to +70°C
RM4559D	D	-55°C to +125°C
RM4559D/883B	D	-55°C to +125°C
RM4559T	T	-55°C to +125°C
RM4559T/883B	T	-55°C to +125°C

### Notes:

/883B suffix denotes Mil-Std-883, Level B processing

N = 8-lead plastic DIP

D = 8 lead ceramic DIP

T = 8-lead metal can (TO-99)

M = 8-lead plastic SOIC

## Absolute Maximum Ratings

### Supply Voltage

RM4559 ..... ±22V

RC4559 ..... ±18V

Input Voltage<sup>1</sup> ..... ±15V

Differential Input Voltage ..... 30V

Output Short Circuit Duration<sup>2</sup> ..... Indefinite

Operating Temperature Range

RM4559 ..... -55°C to +125°C

RC4559 ..... 0°C to +70°C

Lead Soldering Temperature

(SO-8; 10 sec) ..... +260°C

Lead Soldering Temperature

(DIP, TO-99; 60 sec) ..... +300°C

### Notes:

1. For supply voltages less than ±15V, the absolute maximum input voltage is equal to the supply voltage.

2. Short circuit may be to ground on one op amp only. Rating applies to +75°C ambient temperature.

### Thermal Characteristics

	8-Lead Small Outline	8-Lead Plastic DIP	8-Lead Ceramic DIP	8-Lead TO-99 Metal Can
Max. Junction Temp.	+125°C	+125°C	+175°C	+175°C
Max. $P_D T_A < 50^\circ\text{C}$	300 mW	468 mW	833 mW	658 mW
Therm. Res $\theta_{JC}$	—	—	45°C/W	50°C/W
Therm. Res. $\theta_{JA}$	240°C/W	160°C/W	150°C/W	190°C/W
For $T_A > 50^\circ\text{C}$ Derate at	4.17 mW/°C	6.25 mW/°C	8.33 mW/°C	5.26 mW/°C

### Matching Characteristics

( $V_S = \pm 15\text{V}$ ,  $T_A = +25^\circ\text{C}$  unless otherwise specified)

Parameter	Test Conditions	RM/RC4559 Typ	Units
Voltage Gain	$R_L \geq 2\text{ k}\Omega$	±1.0	dB
Input Bias Current		±15	nA
Input Offset Current		±7.5	nA

# RC4559

## Electrical Characteristics

( $V_S = \pm 15V$  and  $T_A = +25^\circ C$  unless otherwise specified)


Parameters	Test Conditions	RM4559			/RC4559			Units
		Min	Typ	Max	Min	Typ	Max	
Input Offset Voltage	$R_S \leq 10k\Omega$		1.0	5.0		2.0	6.0	mV
Input Offset Current			5.0	100		5.0	100	nA
Input Bias Current			40	250		40	250	nA
Input Resistance (Differential Mode)		0.3	1.0		0.3	1.0		MΩ
Large Signal Voltage Gain	$R_L \geq 2k\Omega$ $V_{OUT} = \pm 10V$	50	300		20	300		V/mV
Output Voltage Swing	$R_L \geq 10k\Omega$	±12	±14		±12	±14		V
	$R_L \geq 2k\Omega$	±10	±13		±10	±13		V
	$R_L \geq 600\Omega$	±9.5	±10		±9.5	±10		V
Input Voltage Range		±12	±13		±12	±13		V
Common Mode Rejection Ratio	$R_S \leq 10k\Omega$	80	100		80	100		dB
Power Supply Rejection Ratio	$R_S \leq 10k\Omega$	82	100		82	100		dB
Supply Current	$R_L = \infty$		3.3	5.6		3.3	5.6	mA
Transient Response	$V_{IN} = 20mV$							
Rise Time	$R_L = 2k\Omega$		80			80		nS
Overshoot	$C_L \leq 100pF$		35			35		%
Slew Rate		1.5	2.0		1.5	2.0		V/μS
Unity Gain Bandwidth		3.0	4.0		3.0	4.0		MHz
Power Bandwidth	$V_{OUT} = 20V_{p-p}$	24	32		24	32		kHz
Input Noise Voltage	$F = 20Hz$ to $20kHz$		1.4	2.0		1.4	2.0	μVRMS
Input Noise Current	$F = 20Hz$ to $20kHz$		25			25		pARMS
Channel Separation	Gain = 100, $F = 10kHz$ $R_S = 1k\Omega$		90			90		dB

The following specifications apply for  $RM = -55^\circ C \leq T_A \leq + 125^\circ C$ ,  $RC = 0^\circ C \leq T_A \leq +70^\circ C$  RM4559/RC4559


Input Offset Voltage	$R_S \leq 10k\Omega$			6.0			7.5	mV
Input Offset Current				300			200	nA
Input Bias Current				500			500	nA
Large Signal Voltage Gain	$R_L \geq 2k\Omega$ $V_{OUT} = \pm 10V$	25			15			V/mV
Output Voltage Swing	$R_L \geq 2k\Omega$	±10			±10			V
Supply Current	$R_L = \infty$		4.0	6.6		4.0	6.6	mA

## Typical Performance Characteristics


Input Bias Current vs. Temperature




Input Offset Current vs. Temperature




Input Common Mode Voltage Range vs. Supply Voltage




Open Loop Voltage Gain vs. Frequency



Open Loop Voltage Gain vs. Temperature



Power Consumption vs. Temperature




Linear


# RC4559

## Typical Performance Characteristics (Continued)


Output Voltage Swing vs. Supply Voltage




Output Voltage Swing vs. Load Resistance




Output Voltage Swing vs. Frequency




Quiescent Current vs. Supply Voltage



Transient Response  
Output Voltage vs. Time




Follower Large Signal Pulse Response  
Output Voltage vs. Time




## Typical Performance Characteristics (Continued)


Input Noise Current Density vs. Frequency




Input Noise Voltage Density vs. Frequency




Channel Separation vs. Frequency




Total Harmonic Distortion vs. Output Voltage



Output Voltage Swing vs. Frequency




Total Harmonic Distortion vs. Frequency




# RC4559

## Typical Applications




Stereo Tone Control




## Typical Applications (Continued)

RIAA Preamplifier




65-0242

Triangular-Wave Generator



65-0243


Low Frequency Sine Wave Generator with Quadrature Output



65-0244

# RC4559

## Schematic Diagram



65-0208